

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A DIVISION OF ASHLAND INC.

Valvoline DEXRON®-VI ATF

Valvoline DEXRON®-VI ATF (automatic transmission fluid) is formulated with premium synthetic base stocks and advanced additive technology, and meets all the stringent requirements of General Motors' DEXRON®-VI specification*, which is designed for the modern automatic transmissions in GM vehicles. Valvoline DEXRON®-VI ATF is officially licensed with GM and can be used in new and old GM automatic transmissions. It is fully back-serviceable and can be used wherever DEXRON®-II and/or DEXRON®-III are recommended.

* DEXRON® is a registered trademark of General Motors Corporation.

The Valvoline DEXRON®-VI ATF Advantages:

- Provides consistent shift performance for new and old GM transmissions
- Extends transmission fluid life and prevents fluid breakdown at higher operating temperatures
- Provides excellent oxidative stability under severe conditions
- Reduces sludge and varnish build-up
- Protects transmission gears and allows them to operate smoothly
- Maintains lubricity
- Flows well for cold start-up
- Thoroughly field tested

Approvals

DEXRON®-VI

Exceeds the latest performance requirements of DEXRON®-III, DEXRON®-II

Meets the performance requirements of Allison C-4

Test	Method	Typical Property
Viscosity @ 100°C	ASTM D445	6.0 cSt
Viscosity @ 40°C	ASTM D445	29.5 cSt
Viscosity Index	ASTM D2270	155
Cold Crank Simulation @ -30°C	ASTM D5293	2,900 cP
Brookfield Viscosity @ -40°C	ASTM D2983	12,500 cP
Pour Point	ASTM D5949/5950/6892	-48 °C / -54 °F
Density @ 15°C	ASTM D4052	0.848 g/cm ³ / 7.08 lb/gal
Flash Point	ASTM D92	208 °C / 406 °F
Color	ASTM D1500	7.0
Appearance	Visual	Red
Sulfur	ASTM D4951	1620 ppm
Phosphorus	ASTM D4951	190 ppm

Effective Date: 4/22/2009

Replaces: 1/2/2007

Approved by ZGZ

Doc #231-Rev 3